

610508 ACCESSIBILITY LIFT



PRODUCT SEEN ON
WWW.LEANPAREDMOLIFT.FR



TSL ACCESSIBILITY LIFT – 0,4T – 1,5mx1,12m – 0,9m – 0,08m

Developed and manufactured to lift personnel and disabled persons, this lift is driven by a PLC (EdmoLift UC60 electronics) that operates the sequence in dead man's control, lifts disabled persons between two levels. Fixed positions are defined by the upper, and lower limit switch.

The lift is powder coated to optimize the wear and tear sustainability. Safety frame under the platform stops the downwards movement when being activated.

It is equipped with integrated power packs with plastic cover, located on the back of the column. This enables accessible maintenance and uncomplicated visual inspection.


The PLC offers a guidance during fault tracing by connection a service control unit with buzzer functionality. The buzzer indicates the problem by giving different sequences, easy to translate and circle the problem.

The lift comes with a ramp and emergency lowering functionality to enable lowering of the platform if the power breaks.

Options to the lift are overload protection that prevents the lift to operate when being loaded above 400kg, emergency phone via GSM, siren and gates with interlock for the upper level. Single phase 1-230 VAC option is available.

By investing into this lift with a capacity of 400 kg, equipped with emergency lowering you'll benefit from a lifting stroke of 0,9m and a closed height of 0,08m.

Feel free to contact us for further information about potential modification that would suit the specifications of your project.



610508 TSL ACCESSIBILITY CHARACTERISTICS

TSL DDA LIFT

Capacity: kg	Length platform mm	Width platform mm	Lifting stroke mm	Closed height mm	Hydraulic power pack	Lifting time sec	Voltage VAC	Power kW	Ctrl voltage VDC	IP	Certificate
400	1500	1120	900	80	Integrated	13	3-380	0,75	24	54	CE, Machine directive & EMC

Security feautres: Safety frame on the platform stops downwards movement when being affected. To "re-set", push up button to lift the platform. Emergency lowering.

EdmoLift Solutions SPRL
40, boîte 1, devant l'Aite
4031 – Liège
BELGIUM

Telephone: +33 1 82 88 93 70 / +32 2 808 43 58
Cell.: +33 6 29 81 13 35
Fax: +33 1 82 88 93 71 / +32 2 808 43 59
Org. no.: BE0 897 714 412
E-mail: jerome.laermans@edmolift.se

EdmoLift®
Solutions